

GASURVEYOR 461R

Gas Monitoring in Oil and Gas Tankers

RANGES

- ◆ 0 to 100% LEL Flammable Gas
- ◆ 0 to 100% Vol. Flammable Gas in Inert Gas or Air
- ◆ 0 to 25% Oxygen (O₂)
- ◆ 0 to 100 ppm Hydrogen Sulphide (H₂S)

FEATURES

- ◆ Infrared volume hydrocarbon sensor unaffected by background gas variations
- ◆ Tank sampling in accordance with SOLAS & ISGOTT recommendations
- ◆ Integrated sampling pump for secure sampling
- ◆ Display illuminates under poor ambient lighting conditions
- ◆ Automatic and Manual Datalogging
- ◆ Tank identification
- ◆ Automatic certificate printing
- ◆ Rugged carbon filled polypropylene case for marine use
- ◆ Simple large button operation
- ◆ Intelligent software eliminates operator error

The single instrument solution for your safety monitoring and inerting applications



PROTECTING SHIPPING . . . WORLDWIDE



Gas Measuring Ranges

- 0 to 100% LEL Flammable
- 0 to 100% Volume Flammable
- 0 to 25% Vol. Oxygen (O₂)
- 0 to 100 ppm Hydrogen Sulphide (H₂S)

Response Time

- Flammable: 15 secs to 95%
- O₂: 20 secs to 95%
- H₂S: 30 secs to 95%

Physical Properties

- Weight: 1.7 kg
- Dimensions: 180 x 95 x 105 mm

Accuracy

The Gasurveyor 461R has been designed to meet all current international standards




Environment

- Temperature Limits -10°C to + 40°C
- Humidity: 0 to 95% R.H. non-condensing

Protection

IP54

Certification



Battery Life

Rechargeable: 8 Hours Minimum

Calibration

GMI provides various calibration options, from simple provision of gas cylinders to a complete on-board certificate printing, datalogging, automatic system.

Instrument Management

GMI has been contracted, by shipping companies, to comprehensively manage their inventory of gas detectors.
re: Calibration Logistics etc.

Accessories as Standard

The Gasurveyor 461R instrument is supplied complete with probes, sample line, spare filters, a carrying strap and instruction manual. Accessories are contained in a rugged marine carrying case.

Training CD-ROM

Packaged training solution for on-board use

Ordering Information

Description	Part No.	
Gasurveyor 461R	13677	<input type="checkbox"/>
* Simple Low Cost Charger 240V (UK)	13184	<input type="checkbox"/>
* Smart Charger 240V (UK)	13100	<input type="checkbox"/>

Note: * Items also available with 110V (USA) and 220V (Euro) power supplies. Contact GMI or an approved GMI distributor for details.

Sample Assembly:

** 15m. Conductive Tubing Assembly	13774	<input type="checkbox"/>
** 30m. Conductive Tubing Assembly	13775	<input type="checkbox"/>
** Probe c/w Conductive Tubing Assembly	13777	<input type="checkbox"/>

Note: ** Assembly includes electrically conductive tubing, tube clamping, water filter, dust filter, hands-free kit.

Inchinnan Business Park,
Renfrew, PA4 9RG, Scotland.
Tel: +44 (0) 141-812 3211 Fax: +44 (0) 141-812 7820

www.gmiuk.com
e-mail: sales@gmiuk.com

Service Centre:
Crownhill, 25 Cochran Close,
Milton Keynes, MK8 OAJ
Tel: +44 (0) 1908 568867 Fax: +44 (0) 1908 261056



Certificate No Q/09769



As an ISO 9001 approved company, GMI Ltd's quality assurance programmes demand the continuous assessment and improvement of all GMI products. Information in this leaflet could thus change without notification and does not constitute a product specification. Please contact GMI or their representative if you require more details.

